Scissor Lift License Whitby

Scissor Lift License Whitby - The operation of scissor lifts carries an inherent risk of danger. Whatever type of powered machinery needs right handling in order to prevent accidents resulting in damage or injury. Companies should ensure that staff utilizing this machinery have the required experience.

Unskilled employees should not be allowed by their companies to make use of scissor lifts. The lift is designed to lift materials and people to various heights. Failure to know and fully abide by safety standard could result in injuries for the users or damage to the lift.

For those who use scissor lifts, there is no legislation governing the use of fall protection. However, manufacturers may suggest the utilization of fall protection and in some circumstances tying off in scissor lifts might be required by employer rules, job-specific risk assessments or local rules.

To be able to ensure that the scissor lift is in good working order prior to using the machine, the operator needs to carry out a thorough inspection. This is the operator's duty, even though the unit has already been in service that day. The operator's instruction manual of the equipment contains a pre-operation checklist.

Examples of what to look for when doing a pre-operation check consist of checking tire-inflation pressure, and checking controls in the platform and ground controls in order to make sure they are functioning. When retracting or extending the boom, watch for delayed movement on the fly section that can indicate cables are loose. Whilst operating the controls, make sure that the emergency stop switches are working. Operate functions against the machine's cutout switches. Test the boom control system by cycling a boom lift to the furthest extent of its operating envelope. Safety limiters should stop the unit automatically before it moves into an unstable position, if they are working properly. If they aren't, turn off the lift and make sure that repairs are made before it is used again.

Safe and proper operating measures should be followed always. Levers should be operated with even, controlled pressure. A control lever should never be pushed from one position to the opposite position. The lever must be shifted to neutral, before stopping, and then proceeding in the desired direction. When released, levers and control switches should automatically return to the neutral position. Depress the foot switch before operating platform controls.